

RPC-M12-MR-5CON-PUR-5.0SH

✓ ACTIVE

TE Part # T4161220005-005
TE Internal #: T4161220005-005
M12 A-CODE MALE R/A SINGLE ENDED CABLE
[View on TE.com >](#)



Cable Assemblies > Copper Cable Assemblies > M8/M12 Sensor Cable Assemblies > M12 A-CODE MALE R/A SINGLE ENDED CABLE



Connector Type: **Plug**
Number of Positions: **5**
Keying: **A**
Housing Material: **GF Nylon**
Cable Assembly Type: **M12 Pigtail**

[All M12 A-CODE MALE R/A SINGLE ENDED CABLE \(140\)](#)

Features

Product Type Features

Assembly Type	Pigtail
Connector Type	Plug
Cable Assembly Type	M12 Pigtail
Shielded	Yes

Configuration Features

Number of Positions	5
Keying	A
Configuration	Single-Ended

Body Features

Cable Jacket Color	Gray
--------------------	------

Mechanical Attachment

Screw & Hole Thread Size	M12
Mounting Angle	Right Angle



Housing Features

Housing Material	GF Nylon
------------------	----------

Dimensions

Wire Size	22 AWG
Cable Assembly Length	5000 mm

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2019 (197) Candidate List Declared Against: JUN 2016 (169)
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.

Customers Also Bought





TE Part #7-1393246-0
W23-X1A1G-3=W23/W31



TE Part #6-1393114-5
KUHP-11AT1-120=KU



TE Part #7-1393114-2
KUHP-11DT1-12=KU



TE Part #2-1393118-7
KUP-14D35-24=KU



TE Part #2-34126-2
TERMINAL,SOLIS R 16-14 3 /8



TE Part #3-1393159-3
20C176=SPRING

Documents

Product Drawings

RPC-M12-MR-5CON-PUR-5.0SH

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_T4161220005-005_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_T4161220005-005_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_T4161220005-005_A.3d_stp.zip

English

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

M8/M12 Sensor Actuator Cable Assemblies Datasheet

English

Product Specifications

Product Specification

English

M12 screw connection application specification



English