

Dimmable Constant Current LED Drivers

IZCOxx-018T Series

Product Overview

IZC0xx-018T Series are a range of RoHS compliant single output Constant Current power supplies, of non waterproof design, suitable for indoor LED lighting applications with triac dimming function.

Technical Features:

- Captive terminal screws for ease of installation
- Snap lock cable strain relief
- Over load/short circuit and thermal protection
- Triac Dimming 1-100%
- Leading and trailing edge operation
- Class II product

Applications:

- Residential LED lighting
- Retail Lighting
- LED downlights
- LED Backlighting
- Mood lighting
- Light sculptures

Product Options

æ		Z LED DRIVER Intelligent	
	PRI 220-240V-	LED Solutions www.ied.co.uk IZC050-018T-9500A-SX	
	0	PRI :220-240V~ 50/60Hz 0.11A	
-	0.76-2.5*	SEC : 500mA, 9-36V == Eff : 0.95 ta = -2050c tc = 80'c (W W W 8	
3		Dimmable with leading edge or trailing edge dimmer SELV equivalent	
100			-
		2014-22 0	10

ILS PART NUMBER	Voltage	Current	Power	LED Config.	Operating Temperature	Dimensions
IZC070-018T-9500A-SX	6V-26V	700mA	18W	2-7 White LEDs	-20°C to +50°C	L113xW44xH28mm
IZC050-018T-9500A-SX	9-36V	500mA	18W	3-10 White LEDs	-20°C to +50°C	L113xW44xH28mm
IZC035-018T-9500A-SX	15-52V	350mA	18W	5-14 White LEDs	-20°C to +50°C	L113xW44xH28mm



ATASH


1

www.i-led.co.uk

Specification

•	IP Rating	IPZO
•	Input Voltage	220-240V
•	Input Frequency	50Hz to 60Hz
•	Power Factor	0.95
•	Efficiency	higher than 80%
•	Set Up Time	< 2s
•	Over Load Protection	100-135% of rated output power
•	Over Temperature Protection	Thermal shutdown
•	Dimming Control	Triac controlled 1-100%
•	Storage Temperature	-20°C to +80°C
٠	Lifetime	50K hours full load 25°C
•	Safety Standards	Designed to meet EN61347-1:2001/EN61347-2-13:2001
•	EMI Standards	Meets Emissions to EN 55105,EN61547
•	Weight	108g
•	Input Connections	Screw terminal
•	Output Connections	Screw terminal

Technical Drawing






Intelligent LED Solutions, Unit 2, Berkshire Business Centre, Berkshire Drive, Thatcham, Berkshire, RG19 4EW Telephone : +44 (0)1635 294606 Email: info@i-led.co.uk www.i-led.co.uk A division of Intelligent Group Solutions Ltd H

www.i-led.co.uk

LED Configuration



For further information please contact ILS

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.



© IGS Version V2 July 2015

Intelligent LED Solutions, Unit 2, Berkshire Business Centre, Berkshire Drive, Thatcham, Berkshire, RG19 4EW Telephone : +44 (0)1635 294606 Email: info@i-led.co.uk www.i-led.co.uk A division of Intelligent Group Solutions Ltd

3