

## STRADA-2X2MX-8-VSM

IESNA Type V (square) for wide areas lighting  
such as car parks. New revision.


### TECHNICAL SPECIFICATIONS:

Dimensions	90.0 mm
Height	13.1 mm
Fastening	screw
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	8.6 kg
Quantity in Box	156 pcs
ROHS compliant	yes ⓘ



### MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
STRADA-2X2MX-8-VSM	Multi-lens	PMMA	clear
STRADA-2X2MX-8-SEAL	Seal	Silicone	clear





#### PHOTOMETRIC DATA (MEASURED):




LED LUXEON M/MX  
FWHM Asymmetric  
Efficiency 94 %  
Peak intensity 0.450 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED NV9W149AM  
FWHM Asymmetric  
Efficiency 94 %  
Peak intensity 0.480 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




LED HiLOM SC16 (LH181B)  
FWHM 140.0°  
Efficiency 94 %  
Peak intensity 0.480 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



SEOUL SEMICONDUCTOR


LED Z8Y22  
FWHM Asymmetric  
Efficiency 94 %  
Peak intensity 0.493 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



#### PHOTOMETRIC DATA (SIMULATED):




LED Bridgelux SMD 5050  
FWHM Asymmetric  
Efficiency 94 %  
Peak intensity 0.440 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




#### CITIZEN


LED CLU700/701  
FWHM Asymmetric  
Efficiency 93 %  
Peak intensity 0.460 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
Bender Wirth: 434 Typ 2x2MX HV



LED NFMW48xA  
FWHM Asymmetric  
Efficiency 94 %  
Peak intensity 45.000 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




LED OSCONIQ P 7070  
FWHM Asymmetric  
Efficiency 94 %  
Peak intensity 0.440 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



#### PHOTOMETRIC DATA (SIMULATED):


#### PHILIPS

LED Fortimo FastFlex LED 2x2 70x70 DC G4  
 FWHM Asymmetric  
 Efficiency 94 %  
 Peak intensity 0.410 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### SEOUL SEMICONDUCTOR

LED Z8Y19  
 FWHM Asymmetric  
 Efficiency 93 %  
 Peak intensity 0.488 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:



#### SEOUL SEMICONDUCTOR

LED Z8Y22  
 FWHM Asymmetric  
 Efficiency 94 %  
 Peak intensity 0.630 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:



#### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

#### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/where\\_to\\_buy](http://www.ledil.com/where_to_buy)