

STRADELLA-IP-28-T3

IESNA Type III (medium) beam for roads that are equal to or wider than mounting height. Variant made from PMMA.


TECHNICAL SPECIFICATIONS:

Dimensions	100.0 mm
Height	9.2 mm
Fastening	pin, screw
Colour	clear
Box size	476 x 273 x 247 mm
Box weight	6.3 kg
Quantity in Box	156 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
STRADELLA-IP-28-T3	Multi-lens	PMMA	clear
STRADELLA-28-SEAL	Seal	Silicone	white




PHOTOMETRIC DATA (MEASURED):




LED HiQLED STR28 CR JE2835 4x7 xxx
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.900 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED HiQLED STR28 CR JÐŠ3030 4x7 xxx
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 1.000 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED QUICK FLUX STR28 XD2x14 xxx G8
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.710 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED QUICK FLUX STR28 XP2x14 xxx G7
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.550 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




PHOTOMETRIC DATA (MEASURED):




LED QUICK FLUX STR28 XT2x14 xxx G5
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.600 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED J Series 2835
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.900 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED J Series 3030
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 1.000 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED XD16
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.710 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





PHOTOMETRIC DATA (MEASURED):




LED XP-G3
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.550 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XT-E
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON 3030 2D (Round LES)
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.780 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NF2x757G
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):


OSRAM

LED Duris S5 (2 chip)
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.680 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SAMSUNG

LED HiLOM SC28 (LH181B)
FWHM Asymmetric
Efficiency 93 %
Peak intensity 0.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SAMSUNG

LED HiLOM SM28 (LM301B)
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.850 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SEOUL SEMICONDUCTOR


LED Z5M3
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.540 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED J Series 3030
FWHM Asymmetric
Efficiency 93 %
Peak intensity 0.680 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XP-G
FWHM Asymmetric
Efficiency 91 %
Peak intensity 0.430 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON TX
FWHM Asymmetric
Efficiency 91 %
Peak intensity 0.560 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON V2
FWHM Asymmetric
Efficiency 91 %
Peak intensity 0.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED NF2x757G
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.660 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NVSxE21A
FWHM Asymmetric
Efficiency 92 %
Peak intensity 0.730 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSLOM Square CSSRM2/CSSRM3
FWHM Asymmetric
Efficiency 92 %
Peak intensity 0.540 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSLOM SSL 150
FWHM Asymmetric
Efficiency 91 %
Peak intensity 0.660 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (SIMULATED):

 SEOUL SEMICONDUCTOR LED Z5M1/Z5M2 FWHM Asymmetric Efficiency 93 % Peak intensity 0.530 cd/lm LEDs/each optic 1 Light colour White Required components:	
 SEOUL SEMICONDUCTOR LED Z8Y22 FWHM Asymmetric Efficiency 90 % Peak intensity 0.600 cd/lm LEDs/each optic 1 Light colour White Required components:	
 SEOUL SEMICONDUCTOR LED Z8Y22P FWHM Asymmetric Efficiency 91 % Peak intensity 0.490 cd/lm LEDs/each optic 1 Light colour White Required components:	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

www.ledil.com/where_to_buy

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

www.ledil.com/where_to_buy