



ENGLISH

Datasheet

Stock No. 1864535,1864536

## RS PRO Tin or Nickel Plated Copper Braid



REG. Nr 8319  
Approved to  
VG96936-10

Tested and certified to VG  
96936-10A when supplied  
as Tin plated Copper  
version (-2/).



## Description

Screening braid provides exceptional protection for wire and cable harnesses from electromagnetic, electrostatic and radio frequency interference.

Available in either tin plated or nickel plated copper, providing optical coverage from 93% to 99%. Supplied on an internal former to aid installation and maintain the shape and form of braid in transit and prior to installation.

Article Number	Plating	Internal Dia.	No. of Carriers	Strand Size	Expansion Range		Max Weight.	Reel Size
		mm		mm	Min.mm	Max. mm	Kg/km	m
	Tin	3	16	0.100	2.5	5	14.1	10
	Tin	4	24	0.127	3.5	7.5	23.2	10
	Tin	6	24	0.127	4.5	9.5	29.5	10
	Tin	7.5	24	0.127	7	14	46.3	10
	Tin	10	36	0.127	8	22	58.8	10
	Tin	12.5	36	0.127	11	24	75	10
	Tin	20	48	0.127	16	38	109	10
1864535	Tin	3	16	0.100	2.5	5	14.1	100
	Tin	4	24	0.127	3.5	7.5	23.2	100
	Tin	6	24	0.127	4.5	9.5	29.5	100
	Tin	7.5	24	0.127	7	14	46.3	100
	Tin	10	36	0.127	8	22	58.8	100
	Tin	12.5	36	0.127	11	24	75	100
	Tin	20	48	0.127	16	38	109	100

Article Number	Plating	Internal Dia.	No. of Carriers	Strand Size	Expansion Range		Max Weight.	Reel Size
		mm		mm	Min.mm	Max. mm	Kg/km	m
	Nickle Plated	3	16	0.100	2.5	5	14.1	10
	Nickle Plated	4	24	0.127	3.5	7.5	23.2	10
	Nickle Plated	6	24	0.127	4.5	9.5	29.5	10
	Nickle Plated	7.5	24	0.127	7	14	46.3	10
	Nickle Plated	10	36	0.127	8	22	58.8	10
	Nickle Plated	12.5	36	0.127	11	24	75	10
	Nickle Plated	20	48	0.127	16	38	109	10
1864536	Nickle Plated	3	16	0.100	2.5	5	14.1	100
	Nickle Plated	4	24	0.127	3.5	7.5	23.2	100
	Nickle Plated	6	24	0.127	4.5	9.5	29.5	100
	Nickle Plated	7.5	24	0.127	7	14	46.3	100
	Nickle Plated	10	36	0.127	8	22	58.8	100
	Nickle Plated	12.5	36	0.127	11	24	75	100
	Nickle Plated	20	48	0.127	16	38	109	100