

Data sheet

Art.No.: 41.022.3041.8

Connector RST08i3/2S S1 ZR1SHL KG

RST08i3/2 connector, 2 pole, male, screw connection, application ~50V/-120V, 8A, for cable diameters 4-7mm, coding color pebble grey, color of housing black



Art.No.	41.022.3041.8
EAN	4049088482144
Order Unit	1

Certificates / Approvals



Technical data

General

Rated current	8 A
Rated voltage	50 V / 120 V
Rated impulse voltage	2.5 kV
strain relief	Yes
Pollution degree	3
Lockable	self-locking (unlocking by hand)
Color of coding/ contact carrier	pebble grey
Marking of poles	1, 2
Color of housing inclusive strain relief	black

Connection Data

Cable diameter max.	7 mm
Cable diameter min.	4 mm
Connection cross section solid mm ² max.	1 mm ²
Connection cross section solid mm ² min.	0.2 mm ²
Connection cross section fine stranded mm ² max.	1 mm ²
Connection cross section fine stranded mm ² min.	0.22 mm ²
Terminations per pole	1
sheath strip length	18 mm
Wire strip length	6 mm

Model

Model	male
Connection type	Screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69

Material

Housing material	Polyamide
halogen free	Yes
Contact material	CuZn
Fire load	0 kWh

Insulation components continuous temperature	100 °C
Surface finish	Silver-plated
UL classification housing	UL-V0
UL classification strain relief	UL-V0

Dimensions

Length	41.8 mm
Width	14.9 mm
Height	14.9 mm

Classification

ECLASS 8.1	27440605
ETIM 7.0	EC002560
ETIM 6.0	EC002560
ETIM 5.0	EC002560
ETIM 4.0	EC002560


☐ Diese Maße werden bei Abnahme besonders geprüft

☐ Ausschließlich Prüfmaße

Mit JE gekennzeichnete Maße sind nur für interne Zwecke gültig


F

Gezeichnete Ausführung/drawn version
41.032.3053.1

Auslieferungszustand/
delivery status

5		6	
Teile-Nr. <i>l part-no.</i>	Type	Kodierung <i>l coding</i>	
41.032.3053.1	RST08i3 S S1 ZR1 H SW	C1	
4L.032.3053.1	RST08i3 S 21 ZR1 H SW		
41.032.3043.9	RST08i3 S S1 ZR1SH BL	C2	
4L.032.3043.9	RST08i3 S 21 ZR1SH BL		
41.032.3041.4	RST08i3 S S1 ZR1SHL SG	C3	
4L.032.3041.4	RST08i3 S 21 ZR1SHL SG		
41.032.3051.8	RST08i3 S S1 ZR1SHL KG	C4	
4L.032.3051.8	RST08i3 S 21 ZR1SHL KG		
41.022.3043.1	RST08i3/2S S1 ZR1 H SW	C1	
4L.022.3043.1	RST08i3/2S 21 ZR1 H SW		
41.022.3043.9	RST08i3/2S S1 ZR1SH BL	C2	
4L.022.3043.9	RST08i3/2S 21 ZR1SH BL		
41.022.3041.4	RST08i3/2S S1 ZR1SHL SG	C3	
4L.022.3041.4	RST08i3/2S 21 ZR1SHL SG		
41.022.3041.8	RST08i3/2S S1 ZR1SHL KG	C4	
4L.022.3041.8	RST08i3/2S 21 ZR1SHL KG		

1:1



●=Pol nicht bestückt
1 pole not mounted

Weitere Daten siehe KATALOG oder eKatalog additional data see CATALOG or eCATALOG	www.wieland-electric.com eshop.wieland-electric.com
--	--

Tolerierung Size ISO 14405 © / Tolerance system Size ISO 14405 ©. (This ISO standard describes the envelope principle. According to the envelope principle the deviations of form and parallelism are limited by the size tolerances).					ja/yes ☒ Stoffverbots- und Deklarationsliste nach WN 5020.010 ist einzuhalten. Conformity with Wieland document WN 5020.010 e (list of prohibited / declarable hazardous substances) to be declared!					
Freitoleranz nach General tolerance				CAD - Zeichnung, keine manuellen Änderungen CAD - drawing, no manual modifications allowed			1. Verwendung: First Use:		Blatt: 1 von 1 Sheet: of 1	
	/	 Maßstab / Scale 1:1	Werkstoff / Material			Tag/Date	Name	Zeichnung Nr. / Drawing No. 41.032.3053.1 13K Maße in mm / Dimensions are in mm		Index a
	/				gezeichnet drawn	22.02.2018	Hollet			
	/				geprüft checked					
	/				Normgepr. Stand. check					
	/	Vol.	mm³	Dfl./Srf.	mm²	Ersatz für / Replacement for:				
	/	 wieland www.wieland-electric.com				Type	Benennung/Title			
a	12.03.2020 /						STECKERTEIL_FA_ZE male with strain relief			
Index	Datum / Blatt Date / Sheet									
Änderung / Revision										