

Rittal – The System.

Faster – better – everywhere.

Baying enclosure system VX25 Distribution enclosures – VX 9666.956

Date : Jun 19, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Baying enclosure system VX25 Distribution enclosures – VX 9666.956

created: 19.06.2019 on www.rittal.com/com-en



Product description

Material:	Sheet steel
Surface finish:	Enclosure frame: Dipcoat-primed Door(s), roof, rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Gland plates: Zinc-plated
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
Basis of test:	IEC 61 439-1/-2
Supply includes:	Enclosure frame Door(s) Door hinged on the right, may be swapped to the left Gland plates Rear panel Roof plate
Note:	For 600 mm wide distribution enclosures, please use basicenclosures

Product features

Dimensions:	Width: 850 mm Height: 2000 mm Depth: 400 mm
--------------------	---

Number of doors:	1
Packs of:	1 pc(s).
Weight/pack:	111 kg
Copper weight (kg per piece):	0
EAN:	4028177929562
Customs tariff number:	94032080
ETIM 6.0:	EC000214
ETIM 5.0:	EC000214
eCl@ss 8.0/8.1:	27142409
eCl@ss 7.0/7.1:	27142409
eCl@ss 6.0/6.1:	27142409
eCl@ss 5.1/5.1.4:	27370302
Product description:	VX Distribution enclosure (ISV), WHdepth 850x2000x400 mm, sheet steel, single-door