

# Rittal – The System.

Faster – better – everywhere.

## **Baying enclosure system VX25 Basic enclosure – VX 8245.000**

Date : Jun 14, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Baying enclosure system VX25 Basic enclosure – VX 8245.000

created: 14.06.2019 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

|                                                  |                                                                                                                                                                                                              |
|--------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Material:</b>                                 | Enclosure frame: Sheet steel, 1.5 mm<br>Roof: Sheet steel, 1.5 mm<br>Door: Sheet steel, 2.0 mm<br>Rear panel: Sheet steel, 1.5 mm<br>Gland plates: Sheet steel, 1.5 mm<br>Mounting plate: Sheet steel 3.0 mm |
| <b>Surface finish:</b>                           | Enclosure frame: Dipcoat-primed<br>Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint                                                                                   |
| <b>Colour:</b>                                   | RAL 7035                                                                                                                                                                                                     |
| <b>Protection category<br/>IP to IEC 60 529:</b> | IP 55                                                                                                                                                                                                        |
| <b>Protection category<br/>NEMA:</b>             | NEMA 12                                                                                                                                                                                                      |
| <b>Type rating to UL<br/>508A:</b>               | Type 1,12                                                                                                                                                                                                    |
| <b>IK Code:</b>                                  | IK10                                                                                                                                                                                                         |
| <b>Supply includes:</b>                          | Enclosure frame<br>Door(s)<br>Door hinged on the right, may be swapped to the left<br>Roof plate<br>Rear panel<br>Gland plates<br>Mounting plate<br>2 punched rails 18 x 39 mm<br>Lock: 3 mm double-bit      |

**Basic material:** Sheet steel

## Product features

**Dimensions:** Width: 1200 mm  
Height: 1400 mm  
Depth: 500 mm

**Mounting plate:** Width: 1099 mm  
Height: 1296 mm

**Number of doors:** 2

**Packs of:** 1 pc(s).

**Weight/pack:** 163.5 kg

**EAN:** 4028177813564

**Customs tariff number:** 94032080

**ETIM 6.0:** EC000261

**ETIM 5.0:** EC000261

**eCl@ss 8.0/8.1:** 27180101

**eCl@ss 7.0/7.1:** 27180101

**eCl@ss 6.0/6.1:** 27180101

**eCl@ss 5.1/5.1.4:** 27180101

**Product description:** VX Baying enclosure system, WHD: 1200x1400x500 mm, sheet steel, with mounting plate, single door at the front

## Approvals

**Approvals:** CSA  
Lloyds Register of Shipping  
UL + C-UL

**Certificates:** EAC  
Protection category

**Declarations:** Declaration of conformity