Rittal - The System.

Faster – better – everywhere.

Baying enclosure system VX25, stainless steel Basic enclosure – VX 8452.000

Date : Jun 14 2019



Baying enclosure system VX25, stainless steel Basic enclosure – VX 8452.000

created: 14.06.2019 on www.rittal.com/com-en



Prod	uct (desc	crip	tion
	400	4000	,, , , , , , , , , , , , , , , , , , ,	

Material: Enclosure frame: Stainless steel 1.4301 (AISI 304), 1.5 mm

Roof: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed Door: Stainless steel 1.4301 (AISI 304), 2.0 mm, exterior brushed Rear panel: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed

Gland plates: Stainless steel 1.4301 (AISI 304), 1.5 mm

Mounting plate: Sheet steel 3.0 mm

Surface finish: Enclosure frame and gland plates: Uncoated

Door, roof and rear panel: Exterior brushed, grain size 400

Mounting plate: Zinc-plated

Protection category IP to IEC 60 529:

IP 55

Protection category NEMA:

NEMA 12

IK Code:

IK09

Supply includes:

Enclosure frame

Door(s)

Door hinged on the right, may be swapped to the left

Roof plate Gland plates Rear panel Mounting plate

Lock: 3 mm double-bit 2 punched rails 18 x 39 mm

Note:

Due to the hardness of the material, we recommend using metal multi-tooth screws

2486.400 for the interior installation.

© Rittal 2019

Product features		
Dimensions:	Width: 600 mm Height: 2000 mm Depth: 600 mm	
Mounting plate:	Width: 499 mm Height: 1896 mm	
Number of doors:	1	
Packs of:	1 pc(s).	
Weight/pack:	104.4 kg	
EAN:	4028177920217	
Customs tariff number:	94032080	
ETIM 6.0:	EC000261	
ETIM 5.0:	EC000261	
eCI@ss 8.0/8.1:	27180101	
eCl@ss 7.0/7.1:	27180101	
eCl@ss 6.0/6.1:	27180101	
eCl@ss 5.1/5.1.4:	27180101	
Product description:	VX Baying enclosure system, WHD: 600x2000x600 mm, stainless steel, 1.4301, with mounting plate, single door at the front	
Approvals		
Approvals:	CSA UL + C-UL	
Certificates:	EAC IK-Code	
Declarations:	Declaration of conformity	

© Rittal 2019