

Electronic Components
KEMET
CHARGED.®

Technical drawing of a mechanical part showing front and side views with dimensions.

Front View (Left):

- Top width: T
- Top hole diameter: $\phi 3.2$
- Total height: L
- Bottom hole diameter: 5.08
- Bottom hole offset from left edge: 0.5
- Bottom hole depth: 1.0
- Bottom hole diameter: 0.3
- Bottom hole offset from right edge: 0.3

Side View (Right):

- Top height: H
- Top hole diameter: 2.65
- Mounting surface
- Bottom hole diameter: 2.65
- Bottom hole offset from left edge: 0.3
- Bottom hole diameter: 0.3

Dimensions	
L	18.1mm
H	5mm
T	6.7mm
LL	10mm

Specifications	
Switching Temperature:	125C +/-5C
Temperature Range:	-20/+150C
Contact Type:	Break
Voltage DC:	30 VDC MAX (Opening/Closing) 1500 VAC /1 minute or 1800 VAC /1 second
Current:	0.1 Amps DC MAX (Opening/Closing), 0.1 mAmps MIN (1VDC, Opening/Closing)
Resistance:	300 mOhms MAX (Contact Resistance)
Max Opening/Closing Power:	1 W (DC)
Max Opening/Closing Voltage:	30 V (DC)
Differential Temperature:	10C Maximum

Electronic Components
KEMET
CHARGED.®