



Sample photo

Order symbol: PC M 95 G
Product nbr: 8724318
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074002310
El. number:
Finland: 3423419
Electric No. Denmark: 8212001763
Electric No. Italy: 7201060
Electric No. Sweden: 2536829

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

Dimensions:			Accessories:	
mm:	230	140	95	CHM-3 DIN-35 Mounting rail
inch:	9.1	5.5	3.7	FM-3 DIN-35 Mounting rail
			FP 22046	Wall fastening lug (4 pcs)
Materials:			Rating:	
Material:	Polycarbonate			
Base colour:	RAL 7035 -light grey			
Cover screws material:	Polyamide			
Cover colour:	RAL 7035 -light grey			
Cover screws colour:	Grey			
Gasket material:	Polyurethane			
Temperatures:			Ingress Protection (EN 60529): IP66/67	
Temperature °C (short term):	-40 ... 120 °C		Impact Resistance (EN 62262): IK08	
Temperature °C (continuous):	-40 ... 80 °C		Electrical insulation: Totally insulated	
Temperature °F (short term):	-40 ... 250 °F		Halogen free (DIN/VDE 0472, Part 815): 1	
Temperature °F (continuous):	-40 ... 175 °F		UV resistance: UL 508	
Accessories:			Flammability Rating: UL 746C 5V	
M-MP	Mounting plate		Glow Wire Test (IEC 695-2-1) °C: 960	
			NEMA Class: NEMA 1, 4X, 6, 6P, 12, 13	
			Certificates:	
			Germanischer Lloyd (GL)	
			SGS Fimko	
			Gost R	

PICCOLO 230x140x95-125

