APPLICA	BLE STAN	IDARD											
RATING	OPERATING TEMPERATURE	RANGE	−25 °C TO +85 °C STOR.			RAGE TEMPERATURE GE			-10	°C TO	+60	°C	
	VOLTAGE				ADDI	TOADI E	CADLE						
	CURRENT		SPEC			ICABLE	CABLE						
		1			1101	VO	DI	-011	UDEMENTS			ОТ	
	RUCTION		TEST METHOD				KI	=QU	IREMENTS			QT	AT
GENERAL EXA		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.						Х	Х
MARKING		CONFIRMED VISUALLY.									Χ	Χ	
ENVIRO	NMENTAL	CHARACTERISTICS											
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				NO HEAVY CORROSION RUIN THE FUNCTION.						Х	_
COUN	I D	ESCRIPTI	ON OF REVISIONS		DESIG	NED			CHECK	.ED		DA	IE
<u></u> ▲ REMARK							APPROV	ÆD.	HY. KOI	BAYASHI		18.0	2. 21
							CHECKE		HY. KOBAYASHI		18. 0	2. 21	
						DESIGNED				KISHI		18. 0	
Unless otherwise specified, refer to IEC 60512 (JIS C 5402).						DRAWN		N	MK. INOUE		18.0	2. 06	
Note QT:Q	ualification Te	est AT:As	surance Test X:Applicable Te	ance Test X:Applicable Test			DRAWING NO.			ELC-003295-31-00			
נחכ	S	SPECIFICATION SHEET F				T NO.			RM15TR-C(31)				
HS	HIF	ROSE E	LECTRIC CO., LTD.		CODE NO.		CL109-0		-0080-5-31		4	◮	1/1