Low Profile RJ45,1x1,Bi-color ACTIVE

TE Part # 1888250-2

TE Internal #: 1888250-2

View on TE.com >



Connectors > Modular Jacks & Plugs > RJ45 Connectors











Modular Jack & Plug Interface Type: RJ45

Port Configuration: Single Port
Port Matrix Configuration: 1 x 1

Modular Jacks & Plugs Products: RJ Type Jacks & Plugs

Connector Contact Density: Standard

Features

Product Type Features

Connectors & Connector Components Type	Connector
Modular Jack & Plug Interface Type	RJ45
Modular Jacks & Plugs Products	RJ Type Jacks & Plugs
Modular Connector Style	Jack
Grounding Options	PCB and Panel Ground
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of PCB Ground Tabs	4
Keyed	No
Port Configuration	Single Port
Port Configuration Port Matrix Configuration	Single Port 1 x 1
Port Matrix Configuration	1 x 1
Port Matrix Configuration Connector Contact Density	1 x 1 Standard
Port Matrix Configuration Connector Contact Density Status Indicator	1 x 1 Standard LED
Port Matrix Configuration Connector Contact Density Status Indicator Number of Positions	1 x 1 Standard LED 8

TE Part # 1888250-2 TE Internal #: 1888250-2



Body Features

Shield Plating Material	Nickel
Shield Material	Copper Alloy
Modular Jack Latch Orientation	Standard - Latch Down
Connector Profile	Low
LED Color (Top Left)	Green/Yellow
LED Color (Top Right)	Green/Yellow

Contact Features

Connector Product Type	Connector Assembly
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Current Rating (Max)	.02 A, .6 A
Contact Mating Area Plating Material	Gold
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material Thickness	1.27 μm[50 μin]

Termination Features

Mechanical Attachment

Panel Mount Feature	Without
Connector Mounting Type	Board Mount, Panel

Housing Features

Mating Entry Location	Side
Centerline (Pitch)	1.02 mm[.04 in]
Housing Color	Black
Housing Material	Thermoplastic

Dimensions

PCB Thickness (Recommended)	1.6 mm
PCB Tail Length	2.29 mm[.091 in]
Connector Height	4.2 mm[.165 in]

Usage Conditions

Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]

Operation/Application



Shielded	Yes
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Performance Category	Cat 5
Packaging Features	
Packaging Quantity	40
Packaging Method	Box & Tray, Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2019 (197) Candidate List Declared Against: JAN 2018 (181)
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts

TE Part # 1888250-2 TE Internal #: 1888250-2





Customers Also Bought



TE Part #2149151-1 EMI/Dust Cover, CFP



TE Part #1-1469372-1 ATCA GUIDE MODULE RA MALE



TE Part #6469081-1 HMZD 3PR, RECEPTACLE ASSEMBLY



TE Part #1888250-3 Low Profile,RJ45,1x1,No Led's



TE Part #5223986-1 UPM KEYED GUIDE MODULE



TE Part #2007198-2 SFP+ 1x1 Cage Assembly, Press-Fit



TE Part #2007132-1 SFP+ 1X4 Cage Assembly, Press-



TE Part #5120677-1
Z-PACK HS3 HDR ASSY 6R
30P RH



TE Part #1888653-4
2X1 OFFSET ST/JK WITH LEDS



TE Part #1-6368011-1 STK JK,2X1,SHLD,G/Y BI-CLR LED

Documents

Product Drawings

Low Profile RJ45,1x1,Bi-color

English

CAD Files

Customer View Model
ENG_CVM_CVM_1888250-2_B.2d_dxf.zip

English

3D PDF

Low Profile RJ45,1x1,Bi-color

TE Part # 1888250-2 TE Internal #: 1888250-2



3D

Customer View Model

ENG_CVM_CVM_1888250-2_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1888250-2_B.3d_stp.zip

English

Datasheets & Catalog Pages

Solutions for AdvancedTCA, AdvancedTCA 300, MicroTCA, and AdvancedMC Standards Datasheet 3-1773445-8

English

1-1773464-9_MODULAR_JACKS_SINGLE_PORT_PCB_MOUNT

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_1888250-2_05222018853_dmtec

English

MD_1888250-2_05222018853_dmtec

English

Agency Approvals

UL Report

English