


Electrical Characteristics	Operating Voltage (VAC): 600
Contact Features	Contact Retention : Without Multiple Contact Types : Without Contact Layout : Inline
Termination Features	Termination Method to Wire & Cable : Crimp
Mechanical Attachment	Panel Mount Feature : Without Connector Mounting Type : Cable Mount (Free-Hanging)
Housing Features	Centerline (Pitch) : 6.35 mm [.25 in] UL Flammability Rating : UL 94V-2 Housing Color : Natural Housing Material : Nylon
Dimensions	Length (mm): 52.07 Width (mm): 14.73
Usage Conditions	Operating Temperature Range : -55 - 105 °C [-67 - 221 °F]
Operation/Application	Circuit Application : Power & Signal Assembly Integration Feature : Without
Industry Standards	Glow Wire Rating : Standard Part - Not Glow Wire VDE Tested : Yes CSA File Number : LR7189 UL Rating : Recognized Agency/Standard : CSA, UL Agency/Standard Number : E28476 CSA Rating : Certified
Packaging Features	Packaging Method : Package Packaging Quantity : 1
Other	For Use With : Universal MATE-N-LOK Cap or Header

We are here to help! Get in touch with our product experts. CHAT WITH US 2 \sim EMAIL US 1 CALL US




Compatible Parts





Products with Similar Specs


View All Similar Products




Also in the Series Universal MATE-N-LOK









Customers Also Bought

